

The **RED** MASTER CUTTER

The Red Master Cutter is designed for dirt rings and the deeper depths required by the Cutting industries.

The tear drop sides have been purposely cropped to avoid plowing and provide easier turning. Two inches of additional space between the two tyne bars, and two inches of depth capability have been added to this harrow frame to achieve 0 to 6 inches of depths. 7 inches of depth may be achieved with repetitive harrowing and proper moisture content.

This Harrow has also been successfully used in dirt rings such as barrel racing, team penning, reining, rodeo, etc.

Features of the Red Master Cutter:

- Red Cutter will adjust zero inches to 6 inches of depth, 7 inches with proper conditions
- 4 x 3/16 inch wall thickness structural tubing
- Two rows of spring tynes
- 3-point hitch
- Double braced lift brackets
- Adequate ground clearance when lifted for transport
- Shouldered and nuted high carbon teeth
- Tips are reversible (teeth) for extended life
- Eliminates crusting - breaks up clods and smoothes
- The 3-point lift allows operator to back into corners
- Self cleaning action helps to prevent plugging
- Guide wheels and tires control consistency and depth
- Three tire height adjustments; manufacture setting is in the center hole adjustment
- 650 pound bearing and axle assembly
- Both rows of spring tooth adjust depth with one turnbuckle, while the 3-point supplies additional depth control
- Required HP, 30-50 HP for the 8ft. and the 10ft. Cutter
- Harrow weight for the 8 ft. is 793 lbs. and 863 lbs. for the 10 ft.
- Float Pan is 3/16 " steel gauge with 1/4 " tear drop sides
- Float pan can be removed and exchanged for a Paddle Wheel option (page 10)
- A tow hitch provides towing capability for the Red Roller (page 7)

